

U-Neel®

SUBMERSIBLE PUMPS

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 100 mm (4") OR ABOVE DIA. BOREWELL

Model-UG410R

RADIAL FLOW

Max. Out Side Dia. 97 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM ³ /HR	6.6	7.2	7.8	8.4	9	9.6	10.2	10.8	11.4
						QLPM	110	120	130	140	150	160	170	180	190
						H/Stage	5.3333	4.8333	4.5	4	3.5	3	2.333	1.667	1
1	UG410R	6	0.75	1	38	TOTAL HEAD IN METRES	32	29	27	24	21	18	14	10	6
2	UG410R	9	1.12	1.5	38		46	44	41	36	32	26	20	15	9
3	UG410R	12	1.49	2	38		64	61	56	50	43	35	28	20	12
4	UG410R	18	2.24	3	38		93	87	80	72	63	53	43	32	18
5	UG410R	24	2.98	4	38		125	115	105	94	82	70	55	40	24
6	UG410R	30	3.73	5	38		155	143	130	115	100	85	68	50	30
7	UG410R	35	4.48	6	38		172	159	146	131	115	98	79	58	37

