

U-Neel®

SUBMERSIBLE PUMPS

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 100 mm (4") OR ABOVE DIA. BOREWELL

Max. Out Side Dia. 97 mm

Model-UG411M

Mixed Flow

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM ³ /HR	6.6	7.8	9	10.2	11.4	12.6	13.8	15
						QLPM	110	130	150	170	190	210	230	250
						H/Stage	5.1667	4.6667	4.1667	3.667	3	2.333	1.667	1
1	UG411M	6	0.75	1	50	TOTAL HEAD IN METRES	31	28	25	22	18	14	10	6
2	UG411M	8	1.12	1.5	50		40	36	32	28	24	19	14	9
3	UG411M	10	1.49	2	50		50	46	41	36	30	24	18	12
4	UG411M	12	2.24	3	50		60	54	49	43	36	29	22	15
5	UG411M	14	2.98	4	50		70	64	58	51	43	35	26	17
6	UG411M	16	3.73	5	50		80	73	66	58	49	40	30	20
7	UG411M	18	4.48	6	50		90	83	75	66	57	47	36	25

