

U-Neel®

SUBMERSIBLE PUMPS

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 100 mm (4") OR ABOVE DIA. BOREWELL

Max. Out Side Dia. 97 mm

Model-UG415M

Mixed Flow

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM ³ /HR	9	10.5	12	13.5	15	16.5	18	19.5
						QLPM	150	175	200	225	250	275	300	325
						H/Stage	4	3.6667	3.3333	3	2.667	2.167	1.833	1.333
1	UG415M	6	1.12	1.5	50	TOTAL HEAD IN METRES	24	22	20	18	16	13	11	8
2	UG415M	8	1.49	2	50		34	31	28	25	22	19	15	11
3	UG415M	10	2.24	3	50		39	36	33	29	26	22	18	14
4	UG415M	12	2.98	4	50		47	44	40	36	32	27	22	17
5	UG415M	14	3.73	5	50		54	51	47	43	38	33	28	22
6	UG415M	16	4.48	6	50		64	60	55	50	45	40	34	28

