

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 100 mm (4") OR ABOVE DIA. BOREWELL

Max. Out Side Dia. 97 mm

Model - UG42R

RADIAL FLOW

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	Qm ³ /HR	2.1	2.4	2.7	3	3.3	3.6	3.9	4.2	4.5
						QLPM	35	40	45	50	55	60	65	70	75
						H/Stage	6.625	6	5.375	4.75	3.875	3.125	2.5	1.75	1
1	UG42R	8	0.37	0.5	32	TOTAL HEAD IN METRES	53	48	43	38	31	25	20	14	8
2	UG42R	12	0.56	0.75	32		81	72	63	54	45	37	30	22	12
3	UG42R	15	0.75	1	32		103	92	80	70	58	48	38	29	15
4	UG42R	22	1.12	1.5	32		146	132	115	99	83	67	53	38	20
5	UG42R	25	1.49	2	32		168	150	132	115	96	77	61	45	25
6	UG42R	30	1.49	2	32		203	180	157	136	115	92	73	51	30
7	UG42R	35	2.24	3	32		235	210	185	160	136	110	86	62	35

