

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 100 mm (4") OR ABOVE DIA. BOREWELL

Max. Out Side Dia. 97 mm

Model - UG47R

RADIAL FLOW

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM ³ /HR	4.8	5.4	6	6.6	7.2	7.8	8.4	9	9.6
						QLPM	80	90	100	110	120	130	140	150	160
						H/Stage	5.5	5	4.5	4.125	3.625	3	2.5	1.875	1
1	UG47R	8	0.75	1	38	TOTAL HEAD IN METRES	44	40	36	33	29	24	20	15	8
2	UG47R	12	1.12	1.5	38		66	60	56	50	45	38	30	22	12
3	UG47R	16	1.49	2	38		88	81	75	68	60	50	41	30	16
4	UG47R	22	2.24	3	38		120	110	100	91	80	68	54	37	20
5	UG47R	28	2.98	4	38		145	133	120	107	95	82	65	47	25
6	UG47R	35	3.73	5	38		172	158	145	130	114	96	76	55	32
7	UG47R	40	4.48	6	38		199	181	166	150	130	110	87	65	38

