



FOR SPECIFIC MODELS ONLY

PRICE LIST / PERFORMANCE TABLE OF ENERGY EFFICIENT (STAR RATING) SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model - Type 5K-50

RADIAL FLOW

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type & Stage	HP	KW	Outlet Size mm	ISI Mark	STAR RATING	QM ³ /HR	0	9	9.9	10.8	11.7	15	19.2
							QLPM	0	150	165	180	195	250	320
							H/Stage	10.0	9.0	8.4	7.6	7.25	5.7	3.0
1	5K-50/6	3	2.2	50	ISI	-	TOTAL HEAD IN METRES	60	54	50.5	45.6	43	34	18
2	5K-50/7	4	3	50	ISI	-		70	63	59	53.5	51	40	21
3	5K-50/8	4	3	50	ISI	-		80	72	67	60.8	58	45	24
4	5K-50/9	4	3	50	ISI	-		90	81	75.5	68.5	65	51	27
5	5K-50/10	5	3.7	50	ISI	-		100	90	84	76	73	57	30
6	5K-50/11	5	3.7	50	ISI	-		110	99	92.5	84	80	63	33
7	5K-50/12	6	4.5	50	ISI	-		120	108	100.5	91	87	68	36
8	5K-50/13	6	4.5	50	ISI	-		130	117	109	99	94	74	39
9	5K-50/14	7.5	5.5	50	ISI	-		140	126	117	106	102	79	42
10	5K-50/15	7.5	5.5	50	ISI	-		150	135	126	114	109	85	45
11	5K-50/16	7.5	5.5	50	ISI	-		160	144	134.5	122	116	91.5	48
12	5K-50/17	7.5	5.5	50	ISI	-		170	153	142.5	129.5	123	97	51
13	5K-50/18	10	7.5	50	ISI	-		180	162	151	137	131	102.5	54
14	5K-50/19	10	7.5	50	ISI	-		190	171	159	144.5	138	108	57
15	5K-50/20	10	7.5	50	ISI	-		200	180	167.5	152	145	114	60
16	5K-50/21	10	7.5	50	ISI	-		210	189	176	160	152	120	63
17	5K-50/22	12.5	9.3	50	ISI	-		220	198	184.5	167.5	160	125.5	66
18	5K-50/23	12.5	9.3	50	ISI	-		230	207	192.5	175	167	131	69
19	5K-50/24	12.5	9.3	50	ISI	-		240	216	201	182.5	174	136.5	72
20	5K-50/25	12.5	9.3	50	ISI	-		250	225	209	190	181	142.5	75
21	5K-50/26	12.5	9.3	50	ISI	-		260	234	218	198	189	148.5	78
22	5K-50/27	15	11	50	ISI	-		270	243	226.5	205.5	196	154	81
23	5K-50/28	15	11	50	ISI	-		280	252	234.5	213	203	159.5	84
24	5K-50/29	15	11	50	ISI	-		290	261	243	220.5	210	165	87
25	5K-50/30	15	11	50	ISI	-		300	270	251	228	218	171	90



Cost Per Stage : 880.00