



FOR SPECIFIC MODELS ONLY

PRICE LIST / PERFORMANCE TABLE OF ENERGY EFFICIENT (STAR RATING) SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

**SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL**

**Model - Type 5SB-10**

**Mixed Flow**

**Max. Out Side Dia. 142 mm**

Sr. No.	Pump Type & Stage	HP	KW	Outlet Size mm	ISI Mark	STAR RATING	QM <sup>3</sup> /HR	0	18	20.7	23.4	24.9	34.5	40.8
							QLPM	0	300	345	390	415	575	680
							H/Stage	10	9.5	8.8	8	7.7	6	3
1	5SB-10/4	4	3	75	ISI	-	TOTAL HEAD IN METRES	40	38	35.5	32	31	24	12
2	5SB-10/5	5	3.7	75	ISI			50	48	44	40	39	30	15
3	5SB-10/6	6	4.5	75	ISI	-		60	57	53	48	46	36	18
4	5SB-10/7	7.5	5.5	75	ISI			70	67	62	56	54	42	21
5	5SB-10/8	7.5	5.5	75	ISI			80	76	70.5	64	62	48	24
6	5SB-10/9	10	7.5	75	ISI	-		90	86	79.5	72	69	54	27
7	5SB-10/10	10	7.5	75	ISI			100	95	88	80	77	60	30
8	5SB-10/11	10	7.5	75	ISI	-		110	104	97	88	85	66	33
9	5SB-10/12	12.5	9.3	75	ISI	-		120	114	106	96	93	72	36
10	5SB-10/13	12.5	9.3	75	ISI	-		130	124	114.5	104	100	78	39
11	5SB-10/14	15	11	75	ISI	-		140	133	123.5	112	108	84	42
12	5SB-10/15	15	11	75	ISI	-		150	143	132	120	116	90	45
13	5SB-10/16	17.5	13	75	ISI	-		160	152	141	128	123	96	48
14	5SB-10/17	17.5	13	75	ISI	-		170	162	150	136	131	102	51
15	5SB-10/18	17.5	13	75	ISI	-		180	171	158.5	144	139	108	54
16	5SB-10/19	20	15	75	ISI	-		190	181	167.5	152	146	114	57
17	5SB-10/20	20	15	75	ISI	-		200	190	176	160	154	120	60

