



FOR SPECIFIC MODELS ONLY

PRICE LIST / PERFORMANCE TABLE OF ENERGY EFFICIENT (STAR RATING) SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

**SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL**

Model - Type 5SB-12

Mixed Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type & Stage	HP	KW	Outlet Size mm	ISI Mark	STAR RATING	QM <sup>3</sup> /HR	0	21	24.3	28.0	30.3	36.3	43.2	
								QLPM	0	350	405	468	505	605	720
								H/Stage	10.5	9.8	9.1	8.25	7.9	6.2	3.0
1	5SB-12/4	5	3.7	75	ISI		TOTAL HEAD IN METRES	42	39	36.5	33	32	24.5	12	
2	5SB-12/5	6	4.5	75	ISI	-		53	49	46	41.5	39.5	31	15	
3	5SB-12/6	7.5	5.5	75	ISI			63	59	54.5	49.5	47	37	18	
4	5SB-12/7	7.5	5.5	75	ISI	-		74	69	64	58	55	43.5	21	
5	5SB-12/8	10	7.5	75	ISI			84	78	73	66	63	49.5	24	
6	5SB-12/9	10	7.5	75	ISI			95	88	82	74.5	71	55.5	27	
7	5SB-12/10	12.5	9.3	75	ISI	-		105	98	91	82.5	79	61.5	30	
8	5SB-12/11	12.5	9.3	75	ISI	-		116	108	100.5	91	87	68	33	
9	5SB-12/12	15	11	75	ISI	-		126	118	109	99	95	74	36	
10	5SB-12/13	15	11	75	ISI	-		137	128	118.5	107.5	103	80.5	39	
11	5SB-12/14	17.5	13	75	ISI	-		147	137	127.5	115.5	111	86.5	42	
12	5SB-12/15	17.5	13	75	ISI	-		158	147	136.5	124	119	93	45	
13	5SB-12/16	20	15	75	ISI	-		168	157	145.5	132	126	99	48	

