



FOR SPECIFIC MODELS ONLY

PRICE LIST / PERFORMANCE TABLE OF ENERGY EFFICIENT (STAR RATING) SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model - Type 5SB-15

Mixed Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type & Stage	HP	KW	Outlet Size mm	ISI Mark	STAR RATING	TOTAL HEAD IN METRES							
							QM ³ /HR	0	21.6	26.1	29.9	32.1	37.8	44.4
							QLPM	0	360	435	498	535	630	740
						H/Stage	11	10	9.35	8.5	8.15	6.35	3	
1	5SB-15/3	5	3.7	75	ISI	-	33	30	28.5	25.5	24.5	22.5	9	
2	5SB-15/4	6	4.5	75	ISI	-	44	40	37.5	34	33	25.5	12	
3	5SB-15/5	7.5	5.5	75	ISI		55	50	47	42.5	41	31.5	15	
4	5SB-15/6	10	7.5	75	ISI	-	66	60	56.5	51	49	38	18	
5	5SB-15/7	10	7.5	75	ISI	-	77	70	65.5	59.5	57	44.5	21	
6	5SB-15/8	12.5	9.3	75	ISI	-	88	80	75	68	65.5	51	24	
7	5SB-15/9	12.5	9.3	75	ISI	-	99	90	84.5	76.5	73.5	57	27	
8	5SB-15/10	15	11	75	ISI	-	110	100	93.5	85	81.5	63.5	30	
9	5SB-15/11	15	11	75	ISI	-	121	110	103	93.5	90	70	33	
10	5SB-15/12	17.5	13	75	ISI	-	132	120	112.5	102	98	76.5	36	
11	5SB-15/13	20	15	75	ISI	-	143	130	122	110.5	106	82.5	39	
12	5SB-15/14	20	15	75	ISI	-	154	140	131	119	114	89	42	

