

HIGH HEAD (40 FEET / PER STAGE)

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model - HK-40

Radial Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM ³ /HR	0	4.5	6.9	8.4	9.9	11.4	12.6	18
						QLPM	0	75	115	140	165	190	210	300
						H/Stage	12.2	10	9	8	7	6	5	1
1	HK-40	5	1.5	2	50	TOTAL HEAD IN METRE	61	50	45	40	35	30	25	5
2	HK-40	6	1.5	2	50		73	60	54	48	42	36	30	6
3	HK-40	7	2.2	3	50		86	70	63	56	49	42	35	7
4	HK-40	8	2.2	3	50		98	80	72	64	56	48	40	8
5	HK-40	9	3	4	50		110	90	81	72	63	54	45	9
6	HK-40	10	3	4	50		122	100	90	80	70	60	50	10
7	HK-40	12	3.7	5	50		147	120	108	96	84	72	60	12
8	HK-40	13	3.7	5	50		159	130	117	104	91	78	65	13
9	HK-40	14	4.5	6	50		171	140	126	112	98	84	70	14
10	HK-40	15	4.5	6	50		183	150	135	120	105	90	75	15
11	HK-40	16	4.5	6	50		196	160	144	128	112	96	80	16
12	HK-40	17	5.5	7.5	50		208	170	153	136	119	102	85	17
13	HK-40	18	5.5	7.5	50		220	180	162	144	126	108	90	18
14	HK-40	19	5.5	7.5	50		232	190	171	152	133	114	95	19
15	HK-40	20	5.5	7.5	50		244	200	180	160	140	120	100	20
16	HK-40	21	5.5	7.5	50		256	210	189	168	147	126	105	21
17	HK-40	23	7.5	10	50		281	230	207	184	161	138	115	23
18	HK-40	24	7.5	10	50		293	240	216	192	168	144	120	24
19	HK-40	25	7.5	10	50		305	250	225	200	175	150	125	25
20	HK-40	26	7.5	10	50		317	260	234	208	182	156	130	26
21	HK-40	27	7.5	10	50		330	270	243	216	189	162	135	27
22	HK-40	28	9.3	12.5	50		342	280	252	224	196	168	140	28
23	HK-40	29	9.3	12.5	50		354	290	261	232	203	174	145	29
24	HK-40	30	9.3	12.5	50		366	300	270	240	210	180	150	30
25	HK-40	31	9.3	12.5	50		379	310	279	248	217	186	155	31
26	HK-40	32	9.3	12.5	50		391	320	288	256	224	192	160	32
27	HK-40	33	9.3	12.5	50		403	330	297	264	231	198	165	33
28	HK-40	34	9.3	12.5	50		415	340	306	272	238	204	170	34
29	HK-40	36	11	15	50		440	360	324	288	252	216	180	36
30	HK-40	38	11	15	50		464	380	342	304	266	228	190	38
31	HK-40	40	11	15	50		488	400	360	320	280	240	200	40

