

HIGH HEAD (40 FEET / PER STAGE)

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model - HK-50

Radial Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM ³ /HR	0	5.7	7.8	9.6	11.1	12.6	15.0	18.6
						QLPM	0	95	130	160	185	210	250	310
						H/Stage	12.5	11	10	9	8	7	5	1
1	HK-50	4	1.5	2	50	TOTAL HEAD IN METRE	50	44	40	36	32	28	20	4
2	HK-50	5	1.5	2	50		63	55	50	45	40	35	25	5
3	HK-50	6	2.2	3	50		75	66	60	54	48	42	30	6
4	HK-50	7	3	4	50		88	77	70	63	56	49	35	7
5	HK-50	8	3	4	50		100	88	80	72	64	56	40	8
6	HK-50	9	3	4	50		113	99	90	81	72	63	45	9
7	HK-50	10	3.7	5	50		125	110	100	90	80	70	50	10
8	HK-50	11	3.7	5	50		138	121	110	99	88	77	55	11
9	HK-50	12	4.5	6	50		150	132	120	108	96	84	60	12
10	HK-50	14	5.5	7.5	50		175	154	140	126	112	98	70	14
11	HK-50	15	5.5	7.5	50		188	165	150	135	120	105	75	15
12	HK-50	16	5.5	7.5	50		200	176	160	144	128	112	80	16
13	HK-50	18	7.5	10	50		225	198	180	162	144	126	90	18
14	HK-50	19	7.5	10	50		238	209	190	171	152	133	95	19
15	HK-50	20	7.5	10	50		250	220	200	180	160	140	100	20
16	HK-50	21	7.5	10	50		263	231	210	189	168	147	105	21
17	HK-50	22	9.3	12.5	50		275	242	220	198	176	154	110	22
18	HK-50	24	9.3	12.5	50		300	264	240	216	192	168	120	24
19	HK-50	25	9.3	12.5	50		313	275	250	225	200	175	125	25
20	HK-50	26	9.3	12.5	50		325	286	260	234	208	182	130	26
21	HK-50	28	11	15	50		350	308	280	252	224	196	140	28
22	HK-50	30	11	15	50		375	330	300	270	240	210	150	30
23	HK-50	31	11	15	50		388	341	310	279	248	217	155	31
24	HK-50	32	13	17.5	50		400	352	320	288	256	224	160	32
25	HK-50	36	13	17.5	50		450	396	360	324	288	252	180	36
26	HK-50	38	15	20	50		475	418	380	342	304	266	190	38
27	HK-50	40	15	20	50		500	440	400	360	320	280	200	40

