

### HIGH HEAD (45 FEET / PER STAGE)

SUITABLE FOR **150 mm (6")** OR ABOVE DIA. BOREWELL

Model - HK-60

Radial Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM <sup>3</sup> /HR	0	7.8	10.2	12.6	14.4	15.9	18.0	22.8
						QLPM	0	130	170	210	240	265	300	380
						H/Stage	13.75	11	10	9	8	7	5	1
1	HK-60	3	1.5	2	50	TOTAL HEAD IN METRE	41	33	30	27	24	21	15	3
2	HK-60	4	1.5	2	50		55	44	40	36	32	28	20	4
3	HK-60	5	2.2	3	50		69	55	50	45	40	35	25	5
4	HK-60	6	3	4	50		83	66	60	54	48	42	30	6
5	HK-60	7	3	4	50		96	77	70	63	56	49	35	7
6	HK-60	8	3.7	5	50		110	88	80	72	64	56	40	8
7	HK-60	9	3.7	5	50		124	99	90	81	72	63	45	9
8	HK-60	10	4.5	6	50		138	110	100	90	80	70	50	10
9	HK-60	12	5.5	7.5	50		165	132	120	108	96	84	60	12
10	HK-60	13	5.5	7.5	50		179	143	130	117	104	91	65	13
11	HK-60	15	7.5	10	50		206	165	150	135	120	105	75	15
12	HK-60	16	7.5	10	50		220	176	160	144	128	112	80	16
13	HK-60	17	7.5	10	50		234	187	170	153	136	119	85	17
14	HK-60	20	9.3	12.5	50		275	220	200	180	160	140	100	20
15	HK-60	21	9.3	12.5	50		289	231	210	189	168	147	105	21
16	HK-60	22	9.3	12.5	50		303	242	220	198	176	154	110	22
17	HK-60	23	11	15	50		316	253	230	207	184	161	115	23
18	HK-60	24	11	15	50		330	264	240	216	192	168	120	24
19	HK-60	25	11	15	50		344	275	250	225	200	175	125	25
20	HK-60	26	13	17.5	50		358	286	260	234	208	182	130	26
21	HK-60	27	13	17.5	50		371	297	270	243	216	189	135	27
22	HK-60	28	13	17.5	50		385	308	280	252	224	196	140	28
23	HK-60	29	13	17.5	50		399	319	290	261	232	203	145	29
24	HK-60	30	15	20	50		413	330	300	270	240	210	150	30
25	HK-60	31	15	20	50		426	341	310	279	248	217	155	31
26	HK-60	32	15	20	50		440	352	320	288	256	224	160	32

