

HIGH HEAD (45 FEET / PER STAGE)

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model - HK-70

Radial Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM ³ /HR	0	6.6	9.6	12.6	14.10	15.9	17.4	19.8	24.3
						QLPM	0	110	160	205	235	265	290	330	405
						H/Stage	14.0	12	11	10	9	8	7	5	1
1	HK-70	4	2.2	3	50	56	48	44	40	36	32	28	20	4	
2	HK-70	5	3	4	50	70	60	55	50	45	40	35	25	5	
3	HK-70	6	3	4	50	84	72	66	60	54	48	42	30	6	
4	HK-70	7	3.7	5	50	98	84	77	70	63	56	49	35	7	
5	HK-70	8	4.5	6	50	112	96	88	80	72	64	56	40	8	
6	HK-70	9	4.5	6	50	126	108	99	90	81	72	63	45	9	
7	HK-70	10	5.5	7.5	50	140	120	110	100	90	80	70	50	10	
8	HK-70	11	5.5	7.5	50	154	132	121	110	99	88	77	55	11	
9	HK-70	12	5.5	7.5	50	168	144	132	120	108	96	84	60	12	
10	HK-70	13	7.5	10	50	182	156	143	130	117	104	91	65	13	
11	HK-70	14	7.5	10	50	196	168	154	140	126	112	98	70	14	
12	HK-70	15	7.5	10	50	210	180	165	150	135	120	105	75	15	
13	HK-70	16	7.5	10	50	224	192	176	160	144	128	112	80	16	
14	HK-70	17	9.3	12.5	50	238	204	187	170	153	136	119	85	17	
15	HK-70	18	9.3	12.5	50	252	216	198	180	162	144	126	90	18	
16	HK-70	19	9.3	12.5	50	266	228	209	190	171	152	133	95	19	
17	HK-70	20	11	15	50	280	240	220	200	180	160	140	100	20	
18	HK-70	21	11	15	50	294	252	231	210	189	168	147	105	21	
19	HK-70	22	11	15	50	308	264	242	220	198	176	154	110	22	
20	HK-70	23	11	15	50	322	276	253	230	207	184	161	115	23	
21	HK-70	24	13	17.5	50	336	288	264	240	216	192	168	120	24	
22	HK-70	25	13	17.5	50	350	300	275	250	225	200	175	125	25	
23	HK-70	26	13	17.5	50	364	312	286	260	234	208	182	130	26	
24	HK-70	27	15	20	50	378	324	297	270	243	216	189	135	27	
25	HK-70	28	15	20	50	392	336	308	280	252	224	196	140	28	
26	HK-70	30	15	20	50	420	360	330	300	270	240	210	150	30	
27	HK-70	32	17	22.5	50	448	384	352	320	288	256	224	160	32	

TOTAL HEAD IN METRE

