

### HIGH HEAD (47 FEET / PER STAGE)

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model - HK-80

Radial Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM <sup>3</sup> /HR	0	4.8	9.6	13.5	15.6	17.1	21.9	28.2
						QLPM	0	80	160	225	260	285	365	470
						H/Stage	14.3	13	12	11	10	9	6	1
1	HK-80	4	2.2	3	50	57	52	48	44	40	36	24	4	
2	HK-80	5	3	4	50	72	65	60	55	50	45	30	5	
3	HK-80	6	3.7	5	50	86	78	72	66	60	54	36	6	
4	HK-80	7	4.5	6	50	100	91	84	77	70	63	42	7	
5	HK-80	8	4.5	6	50	114	104	96	88	80	72	48	8	
6	HK-80	9	5.5	7.5	50	129	117	108	99	90	81	54	9	
7	HK-80	10	5.5	7.5	50	143	130	120	110	100	90	60	10	
8	HK-80	11	7.5	10	50	158	143	132	121	110	99	66	11	
9	HK-80	12	7.5	10	50	172	156	144	132	120	108	72	12	
10	HK-80	13	7.5	10	50	186	169	156	143	130	117	78	13	
11	HK-80	14	9.3	12.5	50	200	182	168	154	140	126	84	14	
12	HK-80	15	9.3	12.5	50	215	195	180	165	150	135	90	15	
13	HK-80	16	9.3	12.5	50	229	208	192	176	160	144	96	16	
14	HK-80	17	11	15	50	243	221	204	187	170	153	102	17	
15	HK-80	18	11	15	50	258	234	216	198	180	162	108	18	
16	HK-80	19	11	15	50	272	247	228	209	190	171	114	19	
17	HK-80	20	13	17.5	50	286	260	240	220	200	180	120	20	
18	HK-80	21	13	17.5	50	301	273	252	231	210	189	126	21	
19	HK-80	22	13	17.5	50	315	286	264	242	220	198	132	22	
20	HK-80	23	15	20	50	329	299	276	253	230	207	138	23	
21	HK-80	24	15	20	50	344	312	288	264	240	216	144	24	
22	HK-80	25	15	20	50	358	325	300	275	250	225	150	25	
23	HK-80	26	15	20	50	372	338	312	286	260	234	156	26	
24	HK-80	27	17	22.5	50	386	351	324	297	270	243	162	27	
25	HK-80	28	17	22.5	50	401	364	336	308	280	252	168	28	
26	HK-80	29	17	22.5	50	415	377	348	319	290	261	174	29	
27	HK-80	30	18.5	25	50	429	390	360	330	300	270	180	30	
28	HK-80	31	18.5	25	50	444	403	372	341	310	279	186	31	
29	HK-80	32	18.5	25	50	458	416	384	352	320	288	192	32	

TOTAL HEAD IN METRE

