

HIGH HEAD (50 FEET / PER STAGE) (S.S. PUMP)

SUITABLE FOR **150 mm (6")** OR ABOVE DIA. BOREWELL

SSK-100

Radial Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type & Stage	Motor Rating		Outlet size mm	QM ³ /HR	12	12.6	13.8	15.6	18.6	20.4	21.6	24	26.4	Price for Pump	
		KW	HP			QLPM	200	210	230	260	310	340	360	400		440
						H/Stage	15	14	13	12	10	8	6	4		2
1	SSK-100/3	2.2	3.00	50	TOTAL HEAD IN METRE	45	42	39	36	30	24	18	12	6	7955	
2	SSK-100/4	3	4.00	50		60	56	52	48	40	32	24	16	8	9339	
3	SSK-100/5	3.7	5.00	50		75	70	65	60	50	40	30	20	10	10723	
4	SSK-100/6	4.5	6.00	50		90	84	78	72	60	48	36	24	12	12093	
5	SSK-100/8	5.5	7.50	50		120	112	104	96	80	64	48	32	16	14904	
6	SSK-100/10	7.5	10.00	50		150	140	130	120	100	80	60	40	20	17602	
7	SSK-100/12	9.3	12.50	50		180	168	156	144	120	96	72	48	24	20355	
8	SSK-100/15	11.0	15.00	50		225	210	195	180	150	120	90	60	30	24493	
9	SSK-100/18	13.0	17.50	50		270	252	234	216	180	144	108	72	36	28603	
10	SSK-100/20	15.0	20.00	50		300	280	260	240	200	160	120	80	40	31379	

