

HIGH HEAD (50 FEET / PER STAGE) (S.S. PUMP)

SUITABLE FOR **150 mm (6")** OR ABOVE DIA. BOREWELL

SSK-125

Radial Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type & Stage	Motor Rating		Outlet size mm	QM ³ /HR	12.9	16.2	18.6	20.4	22.2	24.6	27.6	30	33	Price for Pump
		KW	HP		QLPM	215	270	310	340	370	410	460	500	550	
					H/Stage	15	14	13	12	10	8	6	4	2	
1	SSK-125/3	3.0	4.00	50	TOTAL HEAD IN METRE	45	42	39	36	30	24	18	12	6	8200
2	SSK-125/4	3.7	5.00	50		60	56	52	48	40	32	24	16	8	9642
3	SSK-125/5	4.5	6.00	50		75	70	65	60	50	40	30	20	10	11084
4	SSK-125/6	5.5	7.50	50		90	84	78	72	60	48	36	24	12	12540
5	SSK-125/8	7.5	10.00	50		120	112	104	96	80	64	48	32	16	15453
6	SSK-125/10	9.3	12.50	50		150	140	130	120	100	80	60	40	20	18365
7	SSK-125/12	11.0	15.00	50		180	168	156	144	120	96	72	48	24	21250
8	SSK-125/14	13.0	17.50	50		210	196	182	168	140	112	84	56	28	24133
9	SSK-125/16	15.0	20.00	50		240	224	208	192	160	128	96	64	32	27089
10	SSK-125/18	17.0	22.50	50		270	252	234	216	180	144	108	72	36	30151
11	SSK-125/20	18.5	25.00	50		300	280	260	240	200	160	120	80	40	33077
12	SSK-125/24	22.0	30.00	50		360	336	312	288	240	192	144	96	48	38929

