

### HIGH HEAD (50 FEET / PER STAGE) (S.S. PUMP)

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

SSK-150

Radial Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type & Stage	Motor Rating		Outlet size mm	QM <sup>3</sup> /HR	15	18	21.6	23.40	26.10	28.2	30	33	37.2	Price for Pump
		KW	HP		QLPM	250	300	360	390	435	470	500	550	620	
					H/Stage	15	14	13	12	10	8	6	4	2	
1	SSK-150/2	2.2	3.00	50	TOTAL HEAD IN METRE	30	28	26	24	20	16	12	8	4	6858
2	SSK-150/3	3.7	5.00	50		45	42	39	36	30	24	18	12	6	8366
3	SSK-150/4	4.5	6.00	50		60	56	52	48	40	32	24	16	8	9887
4	SSK-150/5	5.5	7.50	50		75	70	65	60	50	40	30	20	10	11401
5	SSK-150/7	7.5	10.00	50		105	98	91	84	70	56	42	28	14	14429
6	SSK-150/8	9.3	12.50	50		120	112	104	96	80	64	48	32	16	15914
7	SSK-150/10	11.0	15.00	50		150	140	130	120	100	80	60	40	20	19014
8	SSK-150/12	13.0	17.50	50		180	168	156	144	120	96	72	48	24	22042
9	SSK-150/13	15.0	20.00	50		195	182	169	156	130	104	78	52	26	23513
10	SSK-150/16	18.5	25.00	50		240	224	208	192	160	128	96	64	32	27225
11	SSK-150/20	22	30.00	50		300	280	260	240	200	160	120	80	40	33077

