

HIGH HEAD (50 FEET / PER STAGE) (S.S. PUMP)

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

SSK-200

Radial Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type & Stage	Motor Rating		Outlet size mm	QM ³ /HR	19.5	25.5	27.6	30	36	43.5	46.5	51	54	Price for Pump
		KW	HP		QLPM	325	425	460	500	600	725	775	850	900	
					H/Stage	15	14	13	11	10	8	6	4	2	
1	SSK-200/2	3.0	4.00	50	TOTAL HEAD IN METRE	30	28	26	22	20	16	12	8	4	7003
2	SSK-200/3	4.5	6.00	50		45	42	39	33	30	24	18	12	6	8560
3	SSK-200/4	5.5	7.50	50		60	56	52	44	40	32	24	16	8	10219
4	SSK-200/5	7.5	10.00	50		75	70	65	55	50	40	30	20	10	11805
5	SSK-200/6	9.3	12.50	50		90	84	78	66	60	48	36	24	12	13390
6	SSK-200/8	11.0	15.00	50		120	112	104	88	80	64	48	32	16	16535
7	SSK-200/9	13.0	17.50	50		135	126	117	99	90	72	54	36	18	18135
8	SSK-200/10	15.0	20.00	50		150	140	130	110	100	80	60	40	20	19736
9	SSK-200/12	18.5	25.00	50		180	168	156	132	120	96	72	48	24	24679
10	SSK-200/15	22.0	30.00	50		225	210	195	165	150	120	90	60	30	29894

