

HIGH HEAD (50 FEET / PER STAGE) (S.S. PUMP)

SUITABLE FOR **150 mm (6")** OR ABOVE DIA. BOREWELL

Model SSK-60

Radial Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	HP	KW	Outlet size mm	QM ³ /HR	4.8	6.60	8.40	9.60	10.8	12	13.2	14.4	15.6
						QLPM	80	110	140	160	180	200	220	240	260
						H/Stage	15	14	13	12	10	8	6	4	2
1	SSK-60	5	3	2.2	50	TOTAL HEAD IN METRE	75	70	65	60	50	40	30	20	10
2	SSK-60	7	4	3	50		105	98	91	84	70	56	42	28	14
3	SSK-60	8	5	3.7	50		120	112	104	96	80	64	48	32	16
4	SSK-60	10	6	4.5	50		150	140	130	120	100	80	60	40	20
5	SSK-60	12	7.5	5.5	50		180	168	156	144	180	96	72	48	24
6	SSK-60	16	10	7.5	50		240	224	208	192	160	128	96	64	32
7	SSK-60	20	12.5	9.3	50		300	280	260	240	200	160	120	80	40
8	SSK-60	24	15	11	50		360	336	312	288	240	192	144	96	48
9	SSK-60	26	17.5	13	50		390	364	338	321	260	208	156	104	52
10	SSK-60	30	20	15	50		440	421	390	360	300	240	180	120	60

