

HIGH HEAD (50 FEET / PER STAGE) (S.S. PUMP)

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

SSK-60

Radial Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type & Stage	Motor Rating		Outlet size mm	QM ³ /HR	Radial Flow										Price for Pump
		KW	HP			TOTAL HEAD IN METRE										
						4.8	6.60	8.40	9.60	10.8	12	13.2	14.4	15.6		
					QLPM	80	110	140	160	180	200	220	240	260		
					H/Stage	15	14	13	12	10	8	6	4	2		
1	SSK-60/5	2.2	3.00	50		75	70	65	60	50	40	30	20	10	10074	
2	SSK-60/7	3	4.00	50		105	98	91	84	70	56	42	28	14	12569	
3	SSK-60/8	3.7	5.00	50		120	112	104	96	80	64	48	32	16	13823	
4	SSK-60/10	4.5	6.00	50		150	140	130	120	100	80	60	40	20	16090	
5	SSK-60/12	5.5	7.50	50		180	168	156	144	110	96	72	48	24	18797	
6	SSK-60/16	7.5	10.00	50		240	224	208	192	160	128	96	64	32	23816	
7	SSK-60/20	9.3	12.50	50		285	266	247	228	190	152	114	76	38	28819	
8	SSK-60/24	11	15.00	50		360	336	312	288	240	192	144	96	48	33793	
9	SSK-60/26	13	17.50	50		390	364	338	321	260	208	156	104	52	34658	
10	SSK-60/30	15	20.00	50		440	421	390	360	300	240	180	120	60	41002	

