

HIGH HEAD (50 FEET / PER STAGE) (S.S. PUMP)

SUITABLE FOR **150 mm (6")** OR ABOVE DIA. BOREWELL

SSK-80

Radial Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type & Stage	Motor Rating		Outlet size mm	QM ³ /HR	7.20	9	10.8	11.40	13.2	15	16.8	18	20.1	Price for Pump
		KW	HP		QLPM	120	150	180	190	220	250	280	300	335	
					H/Stage	15	14	13	12	10	8	6	4	2	
1	SSK-80/4	2.2	3.00	50	TOTAL HEAD IN METRE	60	56	52	48	40	32	24	16	8	9123
2	SSK-80/5	3	4.00	50		75	70	65	60	50	40	30	20	10	10436
3	SSK-80/6	3.7	5.00	50		90	84	78	72	60	48	36	24	12	11805
4	SSK-80/8	4.5	6.00	50		120	112	104	96	80	64	48	32	16	14717
5	SSK-80/10	5.5	7.50	50		150	140	130	120	100	80	60	40	20	17068
6	SSK-80/12	7.5	10.00	50		180	168	156	144	120	96	72	48	24	19736
7	SSK-80/15	9.3	12.50	50		225	210	195	180	150	120	90	60	30	23701
8	SSK-80/18	11.0	15.00	50		270	252	234	216	180	144	108	72	36	27666
9	SSK-80/21	13.0	17.50	50		315	294	273	252	210	168	126	84	42	31630
10	SSK-80/24	15.0	20.00	50		360	336	312	288	240	192	144	96	48	35617

