

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model - Type K-15

RADIAL FLOW

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	Single /Three Phase	QM ³ /HR	0	1.5	2.4	3.6	4.8	5.4	6.0	6.6	7.5	8.4
							QLPM	0	25	40	60	80	90	100	110	125	140
							H/Stage	8.8	8.0	7.4	6.4	5.6	5.0	4.5	3.8	2.8	1.5
1	K-15	6	0.75	1	50	S/T	TOTAL HEAD IN METRES	53	48	44	38	34	30	27	23	17	9
2	K-15	7	0.75	1	50	S/T		61	56	52	45	39	35	31	26	19	10
3	K-15	10	1.1	1.5	50	S/T		88	80	74	64	56	50	45	38	28	15
4	K-15	12	1.5	2	50	S/T		105	96	89	77	67	60	54	45	33	18
5	K-15	13	1.5	2	50	S/T		114	104	96	83	73	65	58	49	36	19
6	K-15	16	1.85	2.5	50	S/T		141	128	118	102	90	80	72	61	45	24
7	K-15	20	2.2	3	50	S/T		176	160	148	128	112	100	90	76	56	30
8	K-15	26	3.0	4	50	T		229	208	192	166	146	130	117	99	72	39
9	K-15	33	3.7	5	50	T		290	264	244	211	185	165	148	125	92	49

