

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model - Type K-50

RADIAL FLOW

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	ISI Mark	QM ³ /HR	0	6	8.4	9.6	10.8	12.6	13.8	15	16.2	18
							QLPM	0	100	140	160	180	210	230	250	270	300
							H/Stage	10.4	9.8	9.2	8.7	8.2	7.4	6.6	5.8	4.9	3.3
1	K-50	4	1.5	2	50	-	41	39	37	35	33	30	26	23	20	13	
2	K-50	5	1.5	2	50	-	50	47	45	43	40	37	32	27	24	16	
3	K-50	6	2.2	3	50	ISI	62	59	55	52	49	44	40	35	29	20	
4	K-50	7	3	4	50	-	73	69	64	61	57	52	46	41	34	23	
5	K-50	8	3	4	50	ISI	83	78	74	70	66	59	53	46	39	26	
6	K-50	9	3	4	50	-	92	86	81	76	73	66	59	50	43	29	
7	K-50	10	3.7	5	50	ISI	104	98	92	87	82	74	66	58	49	33	
8	K-50	11	3.7	5	50	-	112	106	100	93	89	81	71	61	53	35	
9	K-50	12	4.5	6	50	ISI	125	118	110	104	98	89	79	70	59	40	
10	K-50	14	5.5	7.5	50	ISI	145	137	129	122	115	104	92	81	69	46	
11	K-50	15	5.5	7.5	50	ISI	156	147	138	130	123	111	99	89	73	49	
12	K-50	16	5.5	7.5	50	-	164	156	145	137	130	118	104	92	77	52	
13	K-50	18	7.5	10	50	-	185	175	165	155	147	133	117	102	88	58	
14	K-50	19	7.5	10	50	-	195	185	175	164	155	141	124	108	93	61	
15	K-50	20	7.5	10	50	-	207	195	183	173	163	148	131	116	98	65	
16	K-50	21	7.5	10	50	-	215	203	191	181	170	154	137	121	102	67	
17	K-50	22	9.3	12.5	50	-	226	212	201	190	179	162	144	127	108	70	
18	K-50	24	9.3	12.5	50	-	246	232	220	207	195	178	156	139	118	75	
19	K-50	25	9.3	12.5	50	-	256	242	229	215	203	185	161	145	122	77	
20	K-50	26	9.3	12.5	50	-	266	251	237	223	210	192	166	150	126	78	
21	K-50	28	11	15	50	-	286	272	254	240	227	207	180	162	137	82	
22	K-50	30	11	15	50	-	306	290	271	256	243	221	194	173	146	86	
23	K-50	31	11	15	50	-	315	299	279	264	251	228	200	178	151	88	
24	K-50	32	13	17.5	50	-	324	308	287	272	258	234	206	183	155	90	
25	K-50	36	13	17.5	50	-	364	345	319	304	290	262	231	207	173	97	
26	K-50	38	15	20	50	-	385	363	337	321	307	277	244	219	183	100	
27	K-50	40	15	20	50	-	405	380	353	337	322	291	256	230	192	103	

TOTAL HEAD IN METRES

