

### SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

#### Model - K-60

#### RADIAL FLOW

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	ISI Mark	QM <sup>3</sup> /HR	0	7.2	8.4	9.6	12	14.4	15.6	16.8	18	19.2
							QLPM	0	120	140	160	200	240	260	280	300	320
							H/Stage	11.6	11.1	10.7	10.4	9.7	8.7	8.1	7.5	6.7	5.7
1	K-60	3	1.5	2	50	-	35	33	32	31	29	26	24	22	20	17	
2	K-60	4	1.5	2	50	-	45	43	40	38	36	33	31	29	26	22	
3	K-60	5	2.2	3	50	-	58	56	53	51	48	44	41	37	34	28	
4	K-60	6	3	4	50	-	70	66	64	62	58	52	49	45	40	34	
5	K-60	7	3	4	50	ISI	81	78	75	73	68	61	57	52	47	40	
6	K-60	8	3.7	5	50	ISI	93	89	86	83	78	70	65	60	54	46	
7	K-60	9	3.7	5	50	-	104	99	96	93	86	77	71	65	60	51	
8	K-60	10	4.5	6	50	ISI	116	111	107	104	97	87	81	75	67	57	
9	K-60	12	5.5	7.5	50	ISI	139	133	128	125	116	104	97	90	80	68	
10	K-60	13	5.5	7.5	50	-	150	143	138	134	125	112	104	96	85	73	
11	K-60	15	7.5	10	50	ISI	174	166	160	156	145	130	121	112	100	85	
12	K-60	16	7.5	10	50	-	185	177	171	166	155	139	129	119	107	91	
13	K-60	17	7.5	10	50	-	195	187	180	175	164	147	136	126	114	96	
14	K-60	20	9.3	12.5	50	-	232	222	214	208	194	174	162	150	134	114	
15	K-60	21	9.3	12.5	50	-	244	232	222	216	202	182	170	157	140	119	
16	K-60	22	9.3	12.5	50	-	255	242	230	224	210	189	177	164	146	124	
17	K-60	23	11	15	50	-	265	253	241	234	220	197	185	171	153	128	
18	K-60	24	11	15	50	-	276	264	252	245	229	205	193	178	160	132	
19	K-60	25	11	15	50	-	288	274	262	255	238	213	200	184	166	135	
20	K-60	26	13	17.5	50	-	300	285	273	266	247	222	208	191	172	139	
21	K-60	27	13	17.5	50	-	313	296	284	277	256	230	216	198	178	143	
22	K-60	28	13	17.5	50	-	325	307	295	288	265	238	223	205	184	147	
23	K-60	29	13	17.5	50	-	335	318	305	298	274	246	230	212	190	150	
24	K-60	30	15	20	50	-	346	328	315	308	284	255	238	219	197	154	
25	K-60	31	15	20	50	-	357	338	325	318	293	264	246	226	204	158	
26	K-60	32	15	20	50	-	368	348	335	328	302	273	254	232	210	162	

TOTAL HEAD IN METRES

