

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model - K-70

RADIAL FLOW

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM <sup>3</sup> /HR	0	9	12	15	17.1	18	21	24
						QLPM	0	150	200	250	285	300	350	400
						H/Stage	11.7	10.7	10.0	9.0	8.2	7.8	6.2	4.2
1	K-70	4	2.2	3	50	TOTAL HEAD IN METRES	47	43	40	36	33	31	25	17
2	K-70	5	3	4	50		58	53	50	45	41	39	31	21
3	K-70	6	3	4	50		70	63	60	54	49	46	37	25
4	K-70	7	3.7	5	50		82	75	70	63	58	55	44	30
5	K-70	8	4.5	6	50		94	86	80	72	66	63	50	34
6	K-70	9	4.5	6	50		105	96	90	81	73	70	56	38
7	K-70	10	5.5	7.5	50		117	107	100	90	82	78	62	42
8	K-70	11	5.5	7.5	50		128	117	110	99	90	86	68	45
9	K-70	12	5.5	7.5	50		138	126	119	107	97	93	73	48
10	K-70	13	7.5	10	50		152	138	130	117	106	101	80	52
11	K-70	14	7.5	10	50		164	150	140	126	114	109	87	58
12	K-70	15	7.5	10	50		175	160	150	135	123	117	93	63
13	K-70	16	7.5	10	50		185	169	159	144	130	124	99	66
14	K-70	17	9.3	12.5	50		197	179	170	153	139	132	105	70
15	K-70	18	9.3	12.5	50		210	193	181	162	148	140	111	75
16	K-70	19	9.3	12.5	50		220	202	190	171	156	148	116	79
17	K-70	20	11	15	50		234	214	201	181	165	157	123	83
18	K-70	21	11	15	50		245	224	211	190	173	165	129	87
19	K-70	22	11	15	50		255	234	221	199	181	172	135	90
20	K-70	23	11	15	50		265	244	230	207	188	179	140	93
21	K-70	24	13	17.5	50		278	254	240	216	196	186	146	95
22	K-70	25	13	17.5	50		290	265	250	225	204	193	153	97
23	K-70	26	13	17.5	50		300	274	260	234	211	200	159	99
24	K-70	27	15	20	50		313	286	271	243	219	208	165	101
25	K-70	28	15	20	50		325	296	281	252	227	215	171	103
26	K-70	30	15	20	50		347	318	300	270	243	230	183	105
27	K-70	32	17	22.5	50		370	338	320	288	260	245	195	107

