

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BORE WELL

Model - K-80

RADIAL FLOW

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM ³ /HR	0	10.8	13.8	16.8	18.9	19.8	22.8	25.8
						QLPM	0	180	230	280	315	330	380	430
						H/Stage	12.0	11.0	10.0	9.0	8.2	7.8	6.3	4.2
1	K-80	4	2.2	3	50	48	44	40	36	33	31	25	17	
2	K-80	5	3	4	50	60	55	50	45	41	39	31	21	
3	K-80	6	3.7	5	50	73	66	60	54	49	47	38	25	
4	K-80	7	4.5	6	50	85	77	70	63	58	55	45	29	
5	K-80	8	4.5	6	50	96	88	80	72	66	62	50	33	
6	K-80	9	5.5	7.5	50	108	99	90	81	73	70	56	38	
7	K-80	10	5.5	7.5	50	120	110	100	90	82	78	63	42	
8	K-80	11	7.5	10	50	133	121	110	99	90	86	69	46	
9	K-80	12	7.5	10	50	145	132	120	108	97	94	75	50	
10	K-80	13	7.5	10	50	156	143	130	117	106	101	81	53	
11	K-80	14	9.3	12.5	50	169	154	140	126	114	109	88	58	
12	K-80	15	9.3	12.5	50	181	165	150	135	123	117	94	63	
13	K-80	16	9.3	12.5	50	192	176	160	144	130	124	100	67	
14	K-80	17	11	15	50	205	187	170	153	139	132	106	72	
15	K-80	18	11	15	50	217	198	180	162	148	140	112	76	
16	K-80	19	11	15	50	229	209	190	171	156	147	119	80	
17	K-80	20	13	17.5	50	241	220	200	180	165	155	125	84	
18	K-80	21	13	17.5	50	253	231	210	189	173	163	132	88	
19	K-80	22	13	17.5	50	265	242	220	198	181	171	138	92	
20	K-80	23	15	20	50	277	253	230	207	188	179	144	96	
21	K-80	24	15	20	50	289	264	240	216	196	187	150	100	
22	K-80	25	15	20	50	301	275	250	225	204	194	156	104	
23	K-80	26	15	20	50	312	286	260	234	211	201	163	107	
24	K-80	27	17	22.5	50	325	297	270	243	219	209	169	111	
25	K-80	28	17	22.5	50	337	308	280	252	227	217	175	115	
26	K-80	29	17	22.5	50	349	319	290	261	235	225	181	118	
27	K-80	30	18.5	25	50	362	330	300	270	243	233	188	122	
28	K-80	31	18.5	25	50	374	341	310	279	252	241	194	126	
29	K-80	32	18.5	25	50	385	352	320	288	260	248	200	129	

TOTAL HEAD IN METRES

