

U-Neel®

SUBMERSIBLE PUMPS

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Max. Out Side Dia. 142 mm

Model M-12

Mixed Flow

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	ISI Mark	QM ³ /HR	0	15	18	21	24	27	30	36
							QLPM	0	250	300	350	400	450	500	600
							H/Stage	12.6	10.0	9.4	8.6	7.8	7.8	6.3	4.1
1	M-12	3	3	4	65	-	TOTAL HEAD IN METRE	38	31	29	26	25	22	20	13
2	M-12	4	3.7	5	65	ISI		51	41	39	35	33	30	27	17
3	M-12	5	4.5	6	65	ISI		63	51	48	44	40	36	33	22
4	M-12	6	5.5	7.5	65	ISI		76	61	58	52	48	43	40	26
5	M-12	8	7.5	10	65	ISI		101	79	76	68	63	57	52	34
6	M-12	9	7.5	10	65	-		113	88	85	77	71	64	57	37
7	M-12	10	9.3	12.5	65	ISI		126	100	94	86	78	70	63	41
8	M-12	12	11	15	65	ISI		150	120	112	102	92	83	73	48
9	M-12	16	15	20	65	-		198	158	146	133	119	105	90	60

