

SUITABLE FOR 150 mm (6") DIA BORE WELL

Max. Out Side Dia. 142 mm

Model - M-16

Mixed Flow

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	ISI Mark	QM ³ /HR	0	18	24	30	36	42	45	48
							QLPM	0	300	400	500	600	700	750	800
							H/Stage	11.4	10.2	9.2	8.1	6.8	5.2	4.3	3.5
1	M-16	3	3.7	5	65	ISI	TOTAL HEAD IN METRE	38	31	28	24	21	17	15	12
2	M-16	4	4.5	6	65	-		50	41	36	33	27	22	19	15
3	M-16	5	5.5	7.5	65	ISI		65	51	45	40	34	28	24	20
4	M-16	6	7.5	10	65	ISI		72	61	55	48	41	33	28	24
5	M-16	7	9.3	12.5	65	-		84	71	65	57	48	38	32	26
6	M-16	8	9.3	12.5	65	ISI		94	81	75	65	55	43	36	31
7	M-16	9	11	15	65	ISI		104	92	84	73	63	48	40	33
8	M-16	10	11	15	65	-		114	102	92	81	68	52	43	35
9	M-16	12	15	20	65	ISI		133	123	113	100	83	60	49	37
10	M-16	14	17	22.5	65	-		150	133	124	109	90	67	54	40

