

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model - SB-12

Mixed Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	ISI Mark	TOTAL HEAD IN METRE							
							QM ³ /HR	0	21	24.6	29.4	33.6	37.2	43.2
							QLPM	0	350	410	490	560	620	720
							H/Stage	10.5	9.8	9	8	7	6	3
1	SB-12	3	3.0	4	65	-		32	30	27	24	21	18	9
2	SB-12	4	3.7	5	65	ISI		42	39	36	32	28	24	12
3	SB-12	5	4.5	6	65	ISI		53	49	45	40	35	30	15
4	SB-12	6	5.5	7.5	65	ISI		63	59	54	48	42	36	18
5	SB-12	7	5.5	7.5	65	-		74	69	63	56	49	42	21
6	SB-12	8	7.5	10	65	ISI		84	78	72	64	56	48	24
7	SB-12	9	7.5	10	65	-		95	88	81	72	63	54	27
8	SB-12	10	9.3	12.5	65	ISI		105	98	90	80	70	60	30
9	SB-12	11	9.3	12.5	65	-		116	108	99	88	77	66	33
10	SB-12	12	11	15	65	ISI		126	118	108	96	84	72	36
11	SB-12	13	11	15	65	-		137	128	117	104	91	78	39
12	SB-12	14	13	17.5	65	-		147	137	126	112	98	84	42
13	SB-12	15	13	17.5	65	-		158	147	135	120	105	90	45
14	SB-12	16	15	20	65	-		168	157	144	128	112	96	48
15	SB-12	17	15	20	65	-		179	167	153	136	119	102	51
16	SB-12	18	17	22.5	65	-		189	177	162	144	126	108	54
17	SB-12	20	18.5	25	65	-		210	196	180	160	140	120	60

