

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model - SB-15

Mixed Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	ISI Mark	QM ³ /HR	0	21.6	30	33	36	39	44.4
							QLPM	0	360	500	550	600	650	740
							H/Stage	11	10	8.5	8	7	6	3
1	SB-15	3	3.7	5	65	-	TOTAL HEAD IN METRE	33	30	25.5	24	21	18	9
2	SB-15	4	4.5	6	65	ISI		44	40	34	32	28	24	12
3	SB-15	5	5.5	7.5	65	ISI		55	50	42.5	40	35	30	15
4	SB-15	6	7.5	10	65	-		66	60	51	48	42	36	18
5	SB-15	7	7.5	10	65	ISI		77	70	59.5	56	49	42	21
6	SB-15	8	9.3	12.5	65	ISI		88	80	68	64	56	48	24
7	SB-15	9	9.3	12.5	65	-		99	90	76.5	72	63	54	27
8	SB-15	10	11	15	65	ISI		110	100	85	80	70	60	30
9	SB-15	11	11	15	65	-		121	110	93.5	88	77	66	33
10	SB-15	12	13	17.5	65	-		132	120	102	96	84	72	36
11	SB-15	13	15	20	65	-		143	130	110.5	104	91	78	39
12	SB-15	14	15	20	65	-		154	140	119	112	98	84	42
13	SB-15	15	17	22.5	65	-		165	150	128	120	105	90	45
14	SB-15	16	18.5	25	65	-		176	160	136	128	112	96	48

