

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model - SB-20

Mixed Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	ISI Mark	QM ³ /HR	0	30	36	42	48	54	60	66
							QLPM	0	500	600	700	800	900	1000	1100
							H/Stage	11.9	9.7	9.1	8.7	7.8	6.9	5.9	4.4
1	SB-20	3	4.5	6	75	ISI	TOTAL HEAD IN METRE	35	29	27	25	23	20	17	13
2	SB-20	4	5.5	7.5	75	ISI		47	38	36	34	31	27	23	18
3	SB-20	5	7.5	10	75	ISI		59	48	45	43	39	34	29	22
4	SB-20	6	9.3	12.5	75	ISI		71	57	54	51	47	41	35	26
5	SB-20	7	11	15	75	ISI		83	67	63	60	55	48	41	30
6	SB-20	8	11	15	75	ISI		94	77	72	69	62	54	46	35
7	SB-20	9	15	20	75	ISI		106	86	81	77	70	61	52	39
8	SB-20	10	15	20	75	ISI		119	97	91	87	78	69	59	44
9	SB-20	11	17	22.5	75	-		129	107	100	96	86	76	65	47
10	SB-20	12	18.5	25	75	-		140	117	110	105	94	83	71	51
11	SB-20	13	18.5	25	75	-		150	126	118	113	101	90	76	54
12	SB-20	14	22	30	75	-		161	135	127	122	109	97	82	58
13	SB-20	15	22	30	75	-		171	144	135	130	117	104	88	61

