

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model - SB-25

Mixed Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	ISI Mark	QM ³ /HR	0	36	42	48	54	60	66	72
							QLPM	0	600	700	800	900	1000	1100	1200
							H/Stage	13.2	9.6	9.1	8.4	8.0	7.4	6.4	5.3
1	SB-25	3	5.5	7.5	75	-	TOTAL HEAD IN METRE	42	33	30	27	25	22	20	18
2	SB-25	4	7.5	10	75	ISI		57	42	39	36	33	31	27	23
3	SB-25	5	9.3	12.5	75	ISI		67	51	48	45	41	37	31	27
4	SB-25	6	11	15	75	ISI		80	60	56	53	49	44	40	33
5	SB-25	7	13	17.5	75	-		93	70	65	60	57	51	46	38
6	SB-25	8	15	20	75	ISI		106	77	73	67	64	59	51	42
7	SB-25	9	17	22.5	75	-		119	87	82	75	72	66	57	47
8	SB-25	10	18.5	25	75	-		132	96	91	84	80	74	64	53
9	SB-25	11	22	30	75	-		145	106	100	92	88	81	70	58
10	SB-25	12	22	30	75	-		158	115	108	100	95	87	76	63

