

# U-Neel®

## SUBMERSIBLE PUMPS

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

**SUITABLE FOR 175 mm (7") OR ABOVE DIA. BOREWELL (V6 / V7)**

Max. Out Side Dia. 165 mm

Model - SB-40

Mixed Flow

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM <sup>3</sup> /HR	0	36	45	57	66	72	81	87	96	105
						QLPM	0	600	750	950	1100	1200	1350	1450	1600	1750
						H/Stage	20.0	16.0	15.0	14.0	13.0	12.0	11.0	10.0	8.5	6.0
1	SB-40	02	5.5	7.5	75/100	TOTAL HEAD IN METRE	40	32	30	28	26	24	22	20	17	12
2	SB-40	03	9.3	12.5	75/100		60	48	45	42	39	36	33	30	26	18
3	SB-40	04	11	15	75/100		80	64	60	56	52	48	44	40	34	24
4	SB-40	05	15	20	75/100		100	80	75	70	65	60	55	50	42	30

