

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

**SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL**

**Model - MP-50**

**Mixed Flow**

**Max. Out Side Dia. 193 mm**

Sr. No.	Pump Type	Stage	HP	KW	Out let Size mm	ISI Mark	QM <sup>3</sup> /HR	0	9	27	43.5	64.5	82.5	97.5	127.5
							QLPM	0	150	450	725	1075	1375	1625	2125
							H/Stage	21.7	20.6	19.4	17.8	15.6	12.8	10.0	1.1
1	MP-50	2	10	7.5	75	ISI	TOTAL HEAD IN METRE	43	41	39	36	31	26	20	2
2	MP-50	3	15	11	75	ISI		65	62	58	53	47	38	30	3
3	MP-50	4	20	15	75	ISI		87	82	78	71	62	51	40	4
4	MP-50	5	25	18.5	75	ISI		108	103	97	89	78	64	50	6
5	MP-50	6	30	22	75	ISI		130	123	117	107	93	77	60	7
6	MP-50	7	35	26	75	ISI		152	144	136	124	109	89	70	8
7	MP-50	8	40	30	75	ISI		173	164	156	142	124	102	80	9
8	MP-50	9	45	33.5	75	ISI		195	185	175	160	140	115	90	10
9	MP-50	10	50	37	75	ISI		217	206	194	178	156	128	100	11

