

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

**SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL**

**Model - MP-60**

**Mixed Flow**

**Max. Out Side Dia. 193 mm**

Sr. No.	Pump Type	Stage	KW	H.P.	Out let Size mm	ISI Mark	QM <sup>3</sup> /HR	0	30	42	54	66	78	90	96
							QLPM	0	500	700	900	1100	1300	1500	1600
							H/Stage	24.5	21.2	19	17.5	15.5	13.5	10.6	94
1	MP-60	2	9.3	12.5	100	-	TOTAL HEAD IN METRE	49	43	38	35	31	27	21	19
2	MP-60	3	15	20	100	ISI		74	64	57	53	47	41	32	28
3	MP-60	4	20	27	100	ISI		98	86	76	70	62	54	43	38
4	MP-60	5	25	35	100	ISI		123	106	95	88	78	67	53	47
5	MP-60	6	30	40	100	ISI		147	127	114	105	93	81	64	57
6	MP-60	7	34	45	100	ISI		172	149	133	123	110	95	74	60
7	MP-60	9	38.5	52	100	-		221	191	171	158	140	122	95	85

