

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SB-30

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	ISI Mark	QM <sup>3</sup> /HR	0	24	30	36	45	51	57	60
							QLPM	0	400	500	600	750	850	950	1000
							H/Stage	20.3	17.8	17.0	16.0	14.4	13.0	11.8	10.9
1	SB-30	2	4.5	6	75	ISI	TOTAL HEAD IN METRE	40	36	34	31	28	26	24	22
2	SB-30	3	7.5	10	75	ISI		60	53	50	47	42	39	35	33
3	SB-30	4	9.3	12.5	75	ISI		81	71	67	63	56	52	47	44
4	SB-30	5	11	15	75	ISI		101	89	84	79	71	65	59	55
5	SB-30	6	15	20	75	ISI		122	107	102	96	86	78	70	66
6	SB-30	7	15	20	75	ISI		142	125	119	112	100	91	82	76
7	SB-30	8	18.5	25	75	ISI		163	143	136	128	115	104	94	87
8	SB-30	9	20	27	75	ISI		183	160	153	144	130	117	106	98
9	SB-30	10	22	30	75	ISI		203	178	170	160	144	130	118	109
10	SB-30	11	25	34	75	ISI		223	196	187	176	158	143	130	120
11	SB-30	12	25	34	75	ISI		244	214	204	192	172	156	142	132
12	SB-30	13	30	40	75	ISI		264	232	221	208	187	169	154	143
13	SB-30	14	34	45	75	ISI		284	250	238	224	201	182	166	154
14	SB-30	15	34	45	75	ISI		304	268	255	240	216	195	178	165

