

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

**SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL**

Model - SB-40

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	ISI Mark	QM <sup>3</sup> /HR	0	24	36	48	54	60	66	72	78	84
							QLPM	0	400	600	800	900	1000	1100	1200	1300	1400
							H/Stage	22.8	20.4	18.8	17.0	15.8	14.0	12.6	10.8	8.5	6.2
1	SB-40	2	5.5	7.5	75	ISI	TOTAL HEAD IN METRE	45	41	37	34	32	28	25	21	17	12
2	SB-40	3	9.3	12.5	75	ISI		68	61	56	51	47	42	37	32	25	19
3	SB-40	4	11	15	75	ISI		91	82	75	68	63	56	50	43	34	25
4	SB-40	5	15	20	75	ISI		114	102	94	85	79	70	63	54	43	31
5	SB-40	6	18.5	25	75	ISI		137	123	112	102	95	84	75	65	51	38
6	SB-40	7	20	27	75	ISI		160	144	130	119	110	98	88	76	60	44
7	SB-40	8	22	30	75	ISI		183	164	149	136	127	112	100	87	68	50
8	SB-40	9	25	34	75	ISI		205	184	169	153	142	126	113	97	76	56
9	SB-40	10	30	40	75	ISI		228	204	188	170	158	140	126	108	85	62
10	SB-40	11	34	45	75	ISI		250	224	206	187	173	154	138	118	93	68
11	SB-40	12	37	50	75	ISI		273	244	224	204	188	168	150	129	102	74
12	SB-40	13	37	50	75	ISI		296	265	243	221	205	182	163	140	110	80
13	SB-40	14	45	60	75	ISI		320	288	260	238	220	196	176	152	120	87
14	SB-40	15	45	60	75	ISI		342	306	282	255	237	210	189	162	127	93

