

U-Neel®

SUBMERSIBLE PUMPS

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SB-50

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM ³ /HR	0	30	42	54	66	72	84	96
						QLPM	0	500	700	900	1100	1200	1400	1600
						H/Stage	23.8	20.8	19.3	18.0	16.3	15.7	12.8	10.0
1	SB-50	2	7.5	10	100	TOTAL HEAD IN METRE	47	41	39	36	33	31	25	20
2	SB-50	3	11	15	100		71	62	58	54	49	47	38	30
3	SB-50	4	15	20	100		95	83	78	72	66	63	51	40
4	SB-50	5	18.5	25	100		118	103	97	90	82	79	64	50
5	SB-50	6	22	30	100		142	124	117	108	99	94	76	60
6	SB-50	7	25.7	35	100		166	145	136	126	115	110	89	70
7	SB-50	8	30	40	100		190	166	155	144	131	126	102	80
8	SB-50	9	34	45	100		214	187	174	162	147	141	115	90
9	SB-50	10	37	50	100		238	208	193	180	163	157	128	100
10	SB-50	12	45	60	100		286	250	232	216	196	188	154	120

