

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SB-60							Mixed Flow	Max. Out Side Dia. 193 mm							
Sr. No.	Pump Type	Stage	HP	KW	Out let Size mm	ISI Mark	QM ³ /HR	0	39	51	69	87.6	97.8	102.9	127.8
							QLPM	0	650	850	1150	1460	1630	1715	2130
							H/Stage	23.0	20.0	18.5	17.0	14.0	12.0	11.0	1.0
1	SB-60	2	12.5	9.3	100	ISI	TOTAL HEAD IN METRE	46	40	37	34	28	24	22	2
2	SB-60	3	20	15	100	ISI		69	60	56	51	42	36	33	3
3	SB-60	4	25	18.5	100	ISI		92	80	74	68	56	48	44	4
4	SB-60	5	30	22	100	ISI		115	100	93	85	70	60	55	5
5	SB-60	6	35	26	100	ISI		138	120	111	102	84	72	66	6
6	SB-60	7	45	33.5	100	ISI		161	140	130	119	98	84	77	7
7	SB-60	8	50	37	100	ISI		184	160	148	136	112	96	88	8
8	SB-60	10	62	46.5	100	-		230	200	185	170	140	120	110	10
9	SB-60	11	72	53.5	100	-		253	220	204	187	154	132	121	11
10	SB-60	12	72	53.5	100	-		276	240	222	204	168	144	132	12

