

# U-Neel®

## SUBMERSIBLE PUMPS

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

**SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL**

Model - SB-60

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Out let Size mm	ISI Mark	QM <sup>3</sup> /HR	0	36	48	69	84	96	102
							QLPM	0	600	800	1150	1400	1600	1700
							H/Stage	24	21	20	17	14	12.0	11
1	SB-60	2	9.3	12.5	100	ISI	TOTAL HEAD IN METRE	48	42	40	34	28	24	22
2	SB-60	3	15	20	100	ISI		73	63	60	51	42	36	33
3	SB-60	4	18.5	25	100	ISI		97	84	80	68	56	48	44
4	SB-60	5	22	30	100	ISI		120	105	100	85	70	60	55
5	SB-60	6	25	34	100	ISI		144	126	120	102	84	72	66
6	SB-60	7	30	45	100	ISI		168	147	140	110	98	84	77
7	SB-60	8	37	50	100	ISI		192	168	160	136	113	96	88
8	SB-60	10	46.5	62	100	-		240	210	200	170	140	120	110
9	SB-60	11	48.5	65	100	-		264	231	220	187	154	132	121
10	SB-60	12	55	72	100	-		288	252	240	204	169	144	132

