

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SB-70

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Out let Size mm	ISI Mark	QM ³ /HR	0	48	60	72	78	90	96	108
							QLPM	0	800	1000	1200	1300	1500	1600	1800
							H/Stage	24.5	22	20	18	17	15	13.5	8.2
1	SB-70	2	11	15	100	ISI	TOTAL HEAD IN METRE	49	44	40	36	34	30	27	17
2	SB-70	3	15	20	100	ISI		74	66	60	54	51	45	41	25
3	SB-70	4	22	30	100	ISI		98	85	80	72	68	60	54	33
4	SB-70	5	25	34	100	ISI		123	110	100	96	85	75	68	41
5	SB-70	6	34	45	100	-		147	132	120	108	102	90	81	49
6	SB-70	7	37	50	100	ISI		172	154	140	126	119	105	95	58
7	SB-70	9	46.5	62	100	-		221	198	180	162	153	135	122	74
8	SB-70	10	55	72	100	-		245	220	200	180	170	150	135	82
9	SB-70	11	60	82	100	-		270	242	220	198	187	165	149	90
10	SB-70	12	63	85	100	-		294	264	240	216	204	180	162	98

