

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SB-70

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	HP	KW	Out let Size mm	ISI Mark	QM ³ /HR	0	45	62.4	73.5	91.5	102	126	141
							QLPM	0	750	1040	1225	1525	1700	2100	2350
							H/Stage	22.5	20.0	18.0	17.0	15.0	13.8	8.8	2.5
1	SB-70	2	15	11	100	ISI	TOTAL HEAD IN METRE	45	38	36	34	30	28	18	5
2	SB-70	3	20	15	100	ISI		68	57	54	51	45	41	26	8
3	SB-70	4	30	22	100	ISI		90	76	72	68	60	55	35	10
4	SB-70	5	35	26	100	ISI		113	95	90	85	75	69	44	13
5	SB-70	6	45	33.5	100	-		135	114	108	102	90	83	53	15
6	SB-70	7	50	37	100	ISI		158	133	126	119	105	96	61	18
7	SB-70	9	62	46.5	100	-		203	171	162	153	135	124	79	23
8	SB-70	10	72	53.5	100	-		225	190	180	170	150	138	88	25
9	SB-70	11	82	61	100	-		248	209	198	187	165	151	96	28
10	SB-70	12	82	61	100	-		270	228	216	204	180	165	105	30

