

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SB-80

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	HP	KW	Out let Size mm	ISI Mark	QM ³ /HR	0	45.6	70.5	100.5	114	120	138
							QLPM	0	760	1175	1675	1900	2000	2300
							H/Stage	23.3	20.0	18.0	14.7	12.3	11.0	3.3
1	SB-80	2	15	11	125	ISI	TOTAL HEAD IN METRE	47	40	36	29	25	22	7
2	SB-80	3	25	18.5	125	ISI		70	60	54	44	37	33	10
3	SB-80	4	30	22	125	ISI		93	80	72	59	49	44	13
4	SB-80	5	40	30	125	ISI		117	100	90	73	62	55	17
5	SB-80	6	50	37	125	ISI		140	120	108	88	74	66	20
6	SB-80	8	62	46.5	125	-		187	160	144	117	99	88	27
7	SB-80	9	72	53.5	125	-		210	180	162	132	111	99	30
8	SB-80	10	82	61	125	-		233	200	180	147	123	110	33
9	SB-80	11	82	61	125	-		257	220	198	161	136	121	37

Cost Per Stage : 3540.00

