

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

**SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL**

Model - SB-80

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Out let Size mm	ISI Mark	QM <sup>3</sup> /HR	0	60	72	90	108	120	126	132
							QLPM	0	1000	1200	1500	1800	2000	2100	2200
							H/Stage	24.5	20.7	19.6	17.6	14.8	12.2	10.8	8.8
1	SB-80	2	11	15	125	ISI	TOTAL HEAD IN METRE	49	41	40	36	30	25	22	18
2	SB-80	3	18.5	25	125	ISI		74	62	60	54	44	37	33	27
3	SB-80	4	22	30	125	ISI		98	83	79	71	60	50	43	35
4	SB-80	5	30	40	125	ISI		123	104	98	88	74	61	54	44
5	SB-80	6	37	50	125	ISI		147	124	118	106	89	76	65	53
6	SB-80	8	46.5	62	125	-		196	166	158	140	118	98	86	70
7	SB-80	9	55	72	125	-		221	186	176	158	133	110	97	79
8	SB-80	10	60	82	125	-		245	207	196	176	148	122	108	88
9	SB-80	11	63	85	125	-		270	228	216	194	163	134	119	97

