

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

**SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL**

Model - SBR-20

Radial Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Out let Size mm	QM <sup>3</sup> /HR	0	14.4	18	19.8	21.6	23.4	25.2	26.1	28.2	30	33
						QLPM	0	240	300	330	360	390	420	435	470	500	550
						H/Stage	21.4	18.6	17.0	16.0	15.0	14.0	13.0	12.0	10.0	8.0	4.0
1	SBR-20	5	7.5	10	75	TOTAL HEAD IN METRE	107	93	85	80	75	70	65	60	50	40	20
2	SBR-20	6	9.3	12.5	75		128	112	102	96	90	84	78	72	60	48	24
3	SBR-20	7	11	15	75		150	130	119	112	105	98	91	84	70	56	28
4	SBR-20	8	11	15	75		171	149	136	128	120	112	104	96	80	64	32
5	SBR-20	9	15	20	75		193	168	153	144	135	126	117	108	90	72	36
6	SBR-20	10	15	20	75		214	186	170	160	150	140	130	120	100	80	40
7	SBR-20	11	17	22.5	75		235	205	187	176	165	154	143	132	110	88	44
8	SBR-20	12	18.5	25	75		257	223	204	192	180	168	156	144	120	96	48
9	SBR-20	13	18.5	25	75		278	242	221	208	195	182	169	156	130	104	52
10	SBR-20	14	22	30	75		300	260	238	224	210	196	182	168	140	112	56
11	SBR-20	15	22	30	75		321	279	255	240	225	210	195	180	150	120	60

