

U-Neel®

SUBMERSIBLE PUMPS

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SBR-25

Radial Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Out let Size mm	ISI Mark	TOTAL HEAD IN METRE											
							QM ³ /HR	0	15.6	19.8	23.4	26.4	28.8	31.2	33.6	35.4	39	44.4
							QLPM	0	260	330	390	440	480	520	560	590	650	740
H/Stage	20.1	19.0	18.0	17.0	16.0	15.0	14.0	13.0	12.0	10.0	6.0							
1	SBR-25	4	7.5	10	75	ISI	81	76	72	68	64	60	56	52	48	40	24	
2	SBR-25	5	9.3	12.5	75	ISI	101	95	90	85	80	75	70	65	60	50	30	
3	SBR-25	6	11	15	75	ISI	121	114	108	102	96	90	84	78	72	60	36	
4	SBR-25	7	15	20	75	ISI	141	133	126	119	112	105	98	91	84	70	42	
5	SBR-25	8	15	20	75	ISI	161	152	144	136	128	120	112	104	96	80	48	
6	SBR-25	9	18.5	25	75	ISI	181	171	162	153	144	135	126	117	108	90	54	
7	SBR-25	10	18.5	25	75	ISI	201	190	180	170	160	150	140	130	120	100	60	
8	SBR-25	11	20	27	75	ISI	222	209	198	187	176	165	154	143	132	110	66	
9	SBR-25	12	22	30	75	ISI	242	228	216	204	192	180	168	156	144	120	72	

