

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SBR-30 Radial Flow Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Out let Size mm	QM ³ /HR	0	24	27.6	30.6	33	34.8	37.2	39	42	45
						QLPM	0	400	460	510	550	580	620	650	700	750
						H/Stage	21.0	18.0	17.0	16.0	15.0	14.0	13.0	12.0	10.0	8.0
1	SBR-30	3	7.5	10	75	TOTAL HEAD IN METRE	63	54	51	48	45	42	39	36	30	24
2	SBR-30	4	9.3	12.5	75		84	72	68	64	60	56	52	48	40	32
3	SBR-30	5	11	15	75		105	90	85	80	75	70	65	60	50	40
4	SBR-30	6	15	20	75		126	108	102	96	90	84	78	72	60	48
5	SBR-30	7	15	20	75		147	126	119	112	105	98	91	84	70	56
6	SBR-30	8	18.5	25	75		168	144	136	128	120	112	104	96	80	64
7	SBR-30	9	22	30	75		189	162	153	144	135	126	117	108	90	72
8	SBR-30	10	22	30	75		210	180	170	160	150	140	130	120	100	80
9	SBR-30	12	26	35	75		252	216	204	192	180	168	156	144	120	96
10	SBR-30	13	30	40	75		273	234	221	208	195	182	169	156	130	104

