

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

### SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SBR-40

Radial Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Out let Size mm	QM <sup>3</sup> /HR	0	21	28.8	36	39	42	45	48	51	54	58.2
						QLPM	0	350	480	600	650	700	750	800	850	900	970
						H/Stage	23.6	21.9	20.9	19.9	19.0	18.0	17.0	16.0	15.0	13.0	10.0
						TOTAL HEAD IN METRE	71	66	63	60	57	54	51	48	45	39	30
1	SBR-40	3	9.3	12.5	75		94	88	83	79	76	72	68	64	60	52	40
2	SBR-40	4	11	15	75		118	110	105	100	95	90	85	80	75	65	50
3	SBR-40	5	15	20	75		142	132	126	120	114	108	102	96	90	78	60
4	SBR-40	6	18.5	25	75		165	153	147	139	133	126	119	112	105	91	70
5	SBR-40	7	20	27	75		188	175	168	159	152	144	136	128	120	104	80
6	SBR-40	8	22	30	75		212	197	188	179	171	162	153	144	135	117	90
7	SBR-40	9	26	35	75		236	219	209	199	190	180	170	160	150	130	100
8	SBR-40	10	30	40	75		260	241	230	219	209	198	187	176	165	143	110
9	SBR-40	11	34	45	75		284	263	251	239	228	216	204	192	180	156	120
10	SBR-40	12	37	50	75												

