

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SBS-40

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM ³ /HR	0	40.8	46.8	51	55.8	61.8	70.8	76.8
						QLPM	0	680	780	850	930	1030	1180	1280
						H/Stage	21	18	16.5	15	14	12.5	11.5	10.5
1	SBS-40	2	5.5	7.5	75	TOTAL HEAD IN METRE	42	36	33	30	28	25	23	21
2	SBS-40	3	9.3	12.5	75		63	54	50	45	42	38	35	32
3	SBS-40	4	11	15	75		84	72	66	60	56	50	46	42
4	SBS-40	5	15	20	75		105	90	83	75	70	63	58	53
5	SBS-40	6	18.5	25	75		126	108	99	90	84	75	69	63
6	SBS-40	7	20	27	75		147	126	116	105	98	88	81	74
7	SBS-40	8	22	30	75		168	144	132	120	112	100	92	84
8	SBS-40	9	25	35	75		189	162	149	135	126	113	104	95
9	SBS-40	10	30	40	75		210	180	165	150	140	125	115	105
10	SBS-40	11	34	45	75		231	198	182	165	154	138	127	116
11	SBS-40	12	37	50	75		252	216	198	180	168	150	138	126
12	SBS-40	13	37	50	75		273	234	215	195	182	163	150	137
13	SBS-40	14	45	60	75		294	252	231	210	196	175	161	148
14	SBS-40	15	45	60	75		315	270	248	225	210	188	173	159

