

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

**SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL**

Model - SBS-40

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	HP	KW	Outlet Size mm	QM <sup>3</sup> /HR	0	45	48	51	55.8	61.8	70.8	76.8
						QLPM	0	750	800	850	930	1030	1180	1280
						H/Stage	18.5	16.7	15.8	15.0	14.0	12.5	11.5	10.5
1	SBS-40	3	12.5	9.3	75	TOTAL HEAD IN METRE	56	50	48	45	42	38	35	32
2	SBS-40	4	15	11	75		74	67	63	60	56	50	46	42
3	SBS-40	5	20	15	75		93	83	79	75	70	63	58	53
4	SBS-40	6	25	18.5	75		111	100	95	90	84	75	69	63
5	SBS-40	7	27	20	75		130	117	111	105	98	88	81	74
6	SBS-40	8	30	22	75		148	133	127	120	112	100	92	84
7	SBS-40	9	35	26	75		167	150	143	135	126	113	104	95
8	SBS-40	10	40	30	75		185	167	158	150	140	125	115	105
9	SBS-40	11	45	33.5	75		204	183	174	165.6	154	138	127	116
10	SBS-40	12	50	37	75		222	200	190	180	168	150	138	126
11	SBS-40	13	50	37	75		241	217	206	195	182	163	150	137
12	SBS-40	14	62	46.5	75		259	233	222	210	196	175	161	147
13	SBS-40	15	62	46.5	75		278	250	238	225	210	188	173	158

